

Patch cable SC-Isopod SO-F50; 2 x 0,50 mm²; PVC Ø 4,20 mm; grey

Art. No.: 201-0406

ANALOG

OFC



General Data

Article number :	201-0406
Name :	SC-Isopod SO-F50
EAN :	4049371004619
Properties :	Analog
Properties :	OFC oxygen free copper
Application area :	Installation
Application :	Patch cable
Colour :	grey
BPVo-Euroclass :	Fca

Technical Data

Signal transmission :	symmetrical
Construction :	(2LI2Y0,50mm ²)(ST)Y
Jacket material :	PVC
Jacket Ø [mm] :	4,20
Number of Channels (audio) :	1
Inner conductor (audio) :	2
Inner conductor (audio) [mm ²] :	0,50
Inner conductor Ø (audio) [mm] :	0,80
AWG (audio) :	21
Shielding :	AL / PT foil + AL / PT foil + filler strand, tin-plated
Shielding factor [%] :	100
Copper strands (audio) :	7
Copper strand Ø (audio) [mm] :	0,30
Conductor insulation material :	PE
Conductor insulation Ø [mm] :	1,50
Weight per 1 m [g] :	58
Fire load per m [kWh] :	0,07
Style variant :	round
Packing :	200 m spool
Temperature min. [°C] :	-25
Temperature max. [°C] :	70
Width [mm] :	4,2
Height [mm] :	4,2

Electrical Data

Capac. cond./cond. per 1 m (audio) [pF] :	100
Capac. cond./shield. per 1 m (audio) [pF] :	160
Insulation resist. per 1 km [GΩ] :	0,2
Insulation resist. per 1 km (audio) [GΩ] :	0,2
Conductor resistance per 1 km [Ω] :	39
Shield. resistance per 1 km [Ω] :	75