


Speaker cable 2 x 1.5mm² flat



Construction:

Conductor	Stranded bare copper wires, 52 x 0.19 mm, $\varnothing = 1.6$ mm 2 x CU stranded copper wires in figure 8 design according picture
Bridge between elements	0.5mm
Jacket	PVC, transparent, $\varnothing = 3.0 \times 6.5$ mm
Identification	One element with a black stripe

Mechanical properties

Bending radius	without load	4 x D
	with load	8 x D
Temperature range	during operation	-30°C to + 75°C
	during installation	-5°C to + 50°C

Electrical properties

at 20°C ± 5°C

DC resistance		≤ 13 Ω/km
Insulation resistance	(500 V)	≥ 200 MΩxkm
Operating voltage		50/75 V _{AC/DC}
Test Voltage	core/core (50 Hz; 1min)	2000 V _{AC rms}

Technical data

Product Code	Type	Cable Dia. mm	Standard Delivery Length m	Gross weight kg/km	Copper Content	Tensile Force N
92739800	Speaker 2 x 1.5mm ² flat	3.0 x 6.5	1000	40.5	30	150

© PRYSMIAN GROUP 2008, All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group: any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.