

Part Number: 70060



12 PAIR AES/EBU, 24AWG, ISTP, LSZH

Product Description

DIGITAL AUDIO 12 PAIR AES/EBU, 24AWG/0.22mm², ISTP, LSZH

Technical Specifications

Product Overview

Environmental Space:	Indoor
Suitable Applications:	Digital multi-modulation cable; Used in professional studios; For the transmission of analogue and digital audio signals; Designed to meet the requirements of the AES/EBU specification

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	Cross Section	Construction n x D
24	7x32	Bare oxygen free copper	0.22 mm ²	7x0.20 mm

Conductor Count:	24
Total Number of Pairs:	12
AWG Size:	24

Insulation

Type	Material	Nominal Diameter	Diameter +/- Tolerance
Insulation	FPE - Foamed Polyethylene	1.45 mm	0.03 mm

Color Chart

Number	Color
Pair 1 t/m 12	White & Blue

Inner Shield Material

Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Aluminum / Polyester	Beldfoil®	100 %	Stranded tinned copper	24	7x0.20 mm

InnerShield, Table Note:	Aluminum inside
--------------------------	-----------------

Inner Jacket Material

Material	Nominal Diameter	Diameter +/- Tolerance
FRNC / LSZH	3.50 mm	0.10 mm

InnerJacket, Table Note:	Elements are numbered for identification
--------------------------	--

Outer Shield Material

Type	Material	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Foil	Aluminum/Polyester Foil	100 %	Stranded tinned copper	24	7x0.20 mm

Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness
LSZH / FRNC	16.90 mm	1.30 mm

Construction and Dimensions

Cabling

Filler

Cotton (3x)

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR

86.0 Ohm/km

Capacitance

Nom. Capacitance Conductor to Conductor

40 pF/m

Impedance

Frequency [MHz]	Nominal Characteristic Impedance	Nominal Characteristic Tolerance
0.1 - 6	110 Ohm	+/- 15 Ohm

Delay

Nominal Velocity of Propagation (VP) [%]

80 %

Temperature Range

Other Temp Range: -30 to +70 °C

Mechanical Characteristics

Min Bend Radius During Installation: 169 mm

Min Bend Radius During Operation: 253.5 mm

Flammability, LSOH, Toxicity Testing

ISO/IEC Flammability: IEC 60332-1-2

LOI of Jacket: Min. 34 %

Amount of Halogen acc. to IEC 60754-1 & EN50267-1: zero

Part Number

Variants

Item #	Color
70060.00500	VIOLET

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS(Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be instock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.