



# Product: 4731RBUHD3 S1

12 GHz Mini RG-11 BNC Connector

# **Product Description**

RG-11, 12 GHz, UHD, BNC, 3 piece crimp connector, single pack

## **Technical Specifications**

### **Product Overview**

Suitable Applications: HD-SDI, UHD-SDI, Video, Digital Video, SMPTE 2082-1 12 Gb/s UHDTV, SMPTE 2081-1 6 Gb/s UHDTV, SMPTE 424M 3 Gb/s HD-SDI 1080P

## **Physical Characteristics (Overall)**

Packaging:

25 Pack or 100 Bulk

#### Connectors

#### Materials

Description	Material	
Nut	Polished Nickel	
Body	Polished Nickel	
Contact	Brass, Gold Plated	
Insulator	PTFE	

## **Electrical Characteristics**

#### Impedance

Nominal Characteristic Impedance 75 Ohm

#### Return Loss (RL)

Frequency [MHz]	Minimum Return (RL)	
5-1485	15 dB	
1485-3000	10 dB	
3000-6000	7 dB	
6000-12000	4 dB	
Electrical Characte	ristics Notes:	

SMPTE 2082-1 Return Loss or better

## **Mechanical Characteristics**

Footprint/Type:	Coax	
Connector Interface Type:	BNC	
Gender:	Male - plug	
Connector Series Name:	UHD	
Locking:	No	
Tool Compatibility:	Kings KTH-1000, (Crimp Die Pin) KTH-2010, (Crimp Die Sleeve) KTH-2041	
Termination Type:	Crimp	
Cable Center Conductor Diameter Limits:	0.063 - 0.0650 in	
Cable Dielectric Diameter Limits:	0.2795 - 0.2894 in	
Cable Outer Jacket Diameter Limits:	0.3976 - 0.4134 in	

#### **Standards**

RG Type: 11

## Applicable Environmental and Other Programs

Environmental Space:	Indoor	
EU Directive 2000/53/EC (ELV):	Yes	
EU Directive 2011/65/EU (RoHS 2):	Yes	
EU Directive 2012/19/EU (WEEE):	Yes	
EU Directive 2015/863/EU (RoHS 2 amendment):	I): Yes	
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)	
CA Prop 65:	Yes	

#### Suitability

Suitability - Indoor:	Yes
Suitability - Outdoor:	No

#### **Plenum/Non-Plenum**

Plenum (Y/N):	No

## Part Number

Variants			
ltem #	Color	UPC	
4731RBUHD3 S1	No Color	612825405733	

#### **History**

Update and Revision:

Revision Number: 0.26 Revision Date: 03-18-2021

# © 2021 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.