



ASSEMBLY RECOMMENDATION

powerCON® | Chassis mounting

Fastening recommendation for Neutrik powerCON 20 A chassis connectors

- **Rear mounted connectors:**
Versions with countersunk mounting holes: no suffix (example: NAC3MPXXA)
- **Convenient fastening with countersunk screw holes:**
(example: NAC3MPXXA*)

Please see the recommended options including the torque limits below:

		Mounting version & maximum allowable torque M_A	
		Rear assembly	Front assembly
Chassis connector (note mounting hole type)	Screw Type Part number example (screws not included)		
	NAC3MPXXA* (no suffix) <ul style="list-style-type: none"> Countersunk thru holes for countersunk machine screws (e.g.: M3, 4-40) 	50 Ncm	50 Ncm
	NAC3MPXXB* (no suffix) <ul style="list-style-type: none"> Countersunk thru holes for countersunk machine screws (e.g.: M3, 4-40) 	50 Ncm	50 Ncm

Neutrik AG	LI	T: +423 / 237 24 24	F: +423/232 53 93	Neutrik France	FR	T: +33 1/4131 6750	F: +33 1/4131 0511
Neutrik USA Inc.	USA	T: +1 704 / 972 3050	F: +1 704/438 9202	Neutrik Tokyo Ltd.	JP	T: +81 3/3663 4733	F: +81 3/3663 4796
Neutrik (UK) Ltd.	UK	T: +44 1983 / 811 441	F: +44 1983/811 439	Neutrik Hong Kong Ltd.	HK	T: +852/2687 6055	F: +852/2687 6052
Neutrik Vertriebs GmbH	DE/NL/AT/DK	T: +49 8131 / 280 890	F: +49 8131/280 830	Neutrik India Pvt. Ltd.	IND	T: +91/982 05 43 424	F: +91/22 26163 540

Draft. Nr.: BDA 592 V1 | Update: 2020-09-02 | Data subject to change without prior notice. © 2020 NEUTRIK®. NEUTRIK® are registered trademark of Neutrik AG. ALL RIGHTS RESERVED.