



OPERATING & ASSEMBLY INSTRUCTION

NAC3FPX-ST | powerCON TRUE1

APPLIANCE OUTLET - SCREW-TYPE


OPERATING INSTRUCTION

Application:


The powerCON TRUE1 system is certified as connector with breaking capacity according IEC 60320, VDE 0625. It is intended for use as appliance couplers and interconnection couplers. It serves to supply power to an appliance and from an appliance to another equipment. To be installed by qualified person only.

Connector Assignment:


APPLIANCE INLET



APPLIANCE OUTLET





APPLIANCE INLET OUTLET COMBINATION




ASSEMBLY INSTRUCTION

Screw type terminals:
max. Wiresize 2.5 mm² / AWG 14



Panel Cutout (Rear Side)



Find more details of powerCON TRUE1 on www.neutrik.com.

NEUTRIK AG LI T: +423 / 237 24 24 F: +423 / 232 53 93
NEUTRIK USA Inc. USA T: +1 704 / 972 3050 F: +1 704 / 438 9202
NEUTRIK (UK) Ltd. UK T: +44 1983 / 811 441 F: +44 1983 / 811 439
NEUTRIK Vertriebs GmbH DE/NL/AT/DK T: +49 8131 / 280 890 F: +49 8131 / 280 830

NEUTRIK France FR T: +33 1 / 4131 6750 F: +33 1 / 4131 0511
NEUTRIK Tokyo Ltd. JP T: +81 3 / 3663 4733 F: +81 3 / 3663 4796
NEUTRIK Hong Kong Ltd. HK T: +852 / 2687 6055 F: +852 / 2687 6052

Draft. Nr.: BDA 352 / 3102M20181 | Update: 23.09.2013 | Data subject to change without prior notice. ©2013 NEUTRIK®. ALL RIGHTS RESERVED. NEUTRIK® are registered trademark.

www.neutrik.com

NEUTRIK