


XLR PRO FLEX analogue / digital



Application

Audio cables are used in professional broadcasting systems for the transmission of analogue and digital audio signals.

Standards

AES/EBU and analogue Audio

Construction

Conductor	stranded copper wires, bare, diameter 0.60 mm
Insulation	Foam-PE + skin-layer, diameter 1.5 mm
Identification	a – core: white; b – core: blue
Stranding	two cores twisted to the bundle + cotton filler, diameter 3.0 mm
Screen	spiralled wires, CU bare, diameter 3.2 mm
Sheath	DMC FLEX PVC, diameter 6.5 mm ± 0.2 mm black, RAL 9005
Printing	DRAKA – XLR PRO FLEX analogue / digital – 110 Ω

XLR PRO FLEX analogue / digital

Mechanical properties

Minimum bending radius	without load	$\geq 4 \times D$ (D= outer diameter)
	with load	$\geq 8 \times D$ (D= outer diameter)
Temperature range	during operation	- 30° C to + 70° C
	during installation	- 5° C to + 50° C

Electrical properties

at 20°C

Loop resistance		$\leq 175 \Omega/\text{km}$
Insulation resistance	500 V	$\geq 2000 \text{ M}\Omega \cdot \text{km}$
Mutual capacitance	800 Hz	nom. 45 nF/km
Velocity ratio		ca .78%
Test voltage	(DC. 1 min) core/core and core/screen	1000 V
Characteristic impedance	6 MHz	$110 \Omega \pm 10 \%$

Electrical data

at 20°C

Frequency (MHz)	Attenuation (dB/100m)
0.015	0.3
1.0	1.5
4.0	3.8
10.0	6.0
20.0	8.5

Technical data

Product code	Designation	Type	Brand name	Outer diameter mm	Weight kg/km	Standard delivery length m	Drum size PWD/CBS	Gross weight kg	Copper content	Tensile force N
1018270	Li-02YSDY	1x2x0.22 ²	XLR PRO FLEX	6.5	50	1000/200	500/200/310	53.5/10.5	12.2	55

[PRODUCT CODE TABLE]

© PRYSMIAN GROUP 2009, All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group: any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.