



# ASSEMBLY RECOMMENDATION

## speakON® | Chassis mounting

### Fastening recommendation for Neutrik speakON chassis connectors

#### ■ Rear mounted connectors:

- Fast and convenient mounting with **Neutrik A-Screw** self-tapping Plastite® screws: "-2" or "-3" suffix versions (examples: **NL4MDXX-V-2**, **NL4MDXX-V-3**)
- Speed-optimized mounting with countersunk holes and optional **MFD** rear mounting frame: versions without suffixes (example: **NL4MDXX-V**)

#### ■ Front mounted connectors:

- Convenient fastening with countersunk screw holes: (example: **NL4MPXX**)

Please see the recommended options including the torque limits below:

Chassis connector (note mounting hole type)		Screw Type   Part number example (screws not included)		Mounting version & maximum allowable torque $M_A$	
				Rear assembly	Front assembly
		 <b>NL4M*XX-*</b> (no suffix)	<ul style="list-style-type: none"> <li>• Countersunk thru holes for countersunk machine screws (e.g.: M3, 4-40)</li> </ul>		
				<b>90 Ncm</b>	<b>60 Ncm</b>
		 <b>NL4M*XX*-2</b> (-2 suffix)	<ul style="list-style-type: none"> <li>• Mirrored self-tapping screw holes for <b>Neutrik A-screw</b> (rear mount only)</li> </ul>		
				<b>90 Ncm</b>	-
		 <b>NL4M*XX*-3</b> (-3 suffix)	<ul style="list-style-type: none"> <li>• Standard orientation self-tapping screw holes for <b>Neutrik A-screw</b> (rear mount only)</li> </ul>		
				<b>90 Ncm</b>	-

<b>Neutrik AG</b>	<b>LI</b>	T: +423 / 237 24 24	F: +423 / 232 53 93	<b>Neutrik France</b>	<b>FR</b>	T: +33 1 / 4131 6750	F: +33 1 / 4131 0511
<b>Neutrik USA Inc.</b>	<b>USA</b>	T: +1 704 / 972 3050	F: +1 704 / 438 9202	<b>Neutrik Tokyo Ltd.</b>	<b>JP</b>	T: +81 3 / 3663 4733	F: +81 3 / 3663 4796
<b>Neutrik (UK) Ltd.</b>	<b>UK</b>	T: +44 1983 / 811 441	F: +44 1983 / 811 439	<b>Neutrik Hong Kong Ltd.</b>	<b>HK</b>	T: +852 / 2687 6055	F: +852 / 2687 6052
<b>Neutrik Vertriebs GmbH</b>	<b>DE/NL/AT/DK</b>	T: +49 8131 / 280 890	F: +49 8131 / 280 830	<b>Neutrik India Pvt. Ltd.</b>	<b>IND</b>	T: +91 / 982 05 43 424	F: +91 / 22 26163 540

Draft. Nr.: BDA 591 V1 | Update: 2020-05-20 | Data subject to change without prior notice. © 2020 NEUTRIK®, NEUTRIK® are registered trademark of Neutrik AG. ALL RIGHTS RESERVED.